

# GSB/GSB-V

Electronic/Glass Fuses

MIDGET, PC MOUNT & MINIATURE FUSES

## GSB/GSB-V

- Glass body
- Fast-acting
- 5 mm x 20 mm
- 1-1/2" Axial leads optional

1/2A through 10A,  
250VAC, UL and CSA  
Recognized

1/2A through 6-3/10A,  
250VAC, SEMKO Approved

1/2A through 6-3/10A, 250VAC, VDE Approved

IEC-127-2 Standard Sheet 2\*



## STANDARD FUSE AMPERE RATINGS

| Catalog Number | Axial Lead Cat. No | Ampere Rating | Volts | I.R. |
|----------------|--------------------|---------------|-------|------|
| GSB1/2         | GSB-V1/2           | 1/2A          | 250V  | 1    |
| GSB630/1000    | GSB-V630/1000      | 630/1000A     | 250V  | 1    |
| GSB8/10        | GSB0-V8/10         | 8/10A         | 250V  | 1    |
| GSB1           | GSB-V1             | 1A            | 250V  | 1    |
| GSB1-1/4       | GSB-V1-1/4         | 1-1/4A        | 250V  | 1    |
| GSB1-6/10      | GSB-V1-6/10        | 1-6/10A       | 250V  | 1    |
| GSB2           | GSB-V2             | 2A            | 250V  | 1    |
| GSB2-1/2       | GSB-V2-1/2         | 2-1/2A        | 250V  | 1    |
| GSB3-15/100    | GSB-V3-15/100      | 3-15/100A     | 250V  | 1    |
| GSB4           | GSB-V4             | 4A            | 250V  | 2    |
| GSB5           | GSB-V5             | 5A            | 250V  | 3    |
| GSB6-3/10      | GSB-V6-3/10        | 6-3/10A       | 250V  | 4    |
| GSB8           | GSB-V8             | 8A            | 250V  | 5    |
| GSB10          | GSB-V10            | 10A           | 250V  | 6    |

1. 250VAC @ 35A I.R.
2. 250VAC @ 40A I.R.
3. 250VAC @ 50A I.R.
4. 250VAC @ 63A I.R.
5. 250VAC @ 80A I.R.
6. 250VAC @ 100A I.R.

\*IEC Standards for 5x20 mm fuses do not include ratings above 6.3 amperes.